TK 503 Soldadora un cabezal YILMAZ

1.5 kW~1 50~60 Hz 230V	20 Lt/dak.	6~8 bar	W: 59 L: 70 H: 74 cm.	128 kg	115 kg

La Soldadora de un cabezal TK 503 se utiliza para el soldado de las esquinas de los perfiles de PVC con el proceso de soldadura en el intervalo de 30° – 180°.

- Realización de soldadura preciso en todos los ángulos del intervalo de 30° – 180°.
- Ajuste de los parámetros desde el panel de control tales como el tiempo de fusión y unión, la presión de la soldadura.
- Inicio y apagado automático del proceso de soldadura.
- Regulación de temperatura entre 0°C – 300°C gracias al termostato electrónico.
- Proceso fácil de la soldadura de los perfiles largos gracias a los brazos de soporte de los perfiles.
- Facilidad en la sustitución del teflón y la limpieza de las placas.
- Función de de operación automática con el intervalo de soldadura de estándar (2 mm) ocero (0.2 mm) según el grosor de la soldadura.
- Los brazos de soporte de perfiles son estándares en ambas direcciones.
- Fijación de perfiles por separado con el pedal de pie.
- Ahorro de tiempo gracias al sistema practico de sustitución de moldes de soldadura.
- Soporte de máquina portátil.

ACCESORIOS OPCIONALES

- Máquina especifica a la altura de la soldadurade 165 mm
- Moldes de soldadura especiales por encargo

- Enable the welding of all angles between 30°-180°infinitely adjustable.
- All parameters such as melting and welding time, welding pressure are set independently.
- Automatically start and finish the welding cycle.
- Adjusting the heat between 0-300°C by means of the electronic thermostat.
- Smooth welding operations for long pro files by means of rotating support arms.
- Maintenance friendly, for example clean ing of the heater plate and changing of the Teflon is very easy by means of quick change system.
- Practical adjustment of standardl (2 mm) or seamless (0.2 mm) welding options manually.
- Standard equipped with height adjustable profile support arms on both side.
- Clamping the profiles separately via foot pedal.
- Saving of time by means of practical mold change feature.
- Portable machine stand.

OPTIONAL ACCESSORIES

- Machine according to the profile height of 165 mm.
- Special welding molds.